

DIGITAL INDICATOR

AX-40



PRECISION CONTROL

Overview

The ASHE Series AX is a range of fully configurable micro-controller based universal Digital process Indicator with and without control relay outputs, offered in a highly compact, rugged and reliable execution. The instrument has three keys on the front panel, with which the operator can set the parameters and configure the instrument as desired. Single or Dual four-digit LED display options are offered on the front panel. The display can indicate any scale range between -999 to +9999 units.

The Indicators accept all industrial standard input signals, like 4 to 20 mA DC, AC/DC Voltage, AC/DC Current, Resistance, Strain-gauge, Frequency and all temperature sensors like RTD Pt-100, Thermocouples (type J,K,R,S,T,B.E.etc.), Proximity Switches, etc. The Indicator is available in several dimensions in panel-mount execution and operates on AC or DC power supply, as required. The instrument may be used in either two-wire or four-wire configuration and is calibrated as specified.

Options include Dual display, multiple Relay outputs, analog retransmission signals, DIN rail mount / weather-proof / flame-proof executions, etc.

The Ashe AX range of Indicators offer a high degree of reliability owing to their inherent accuracy in process control, besides other characteristics like total immunity to shocks, dust, ambient temperatures, humidity and corrosive atmospheres. Further, the instruments are manufactured using selected high-grade components which guarantee their functional reliability and long operational life.

All ASHE range of Digital Indicators carry a lifetime warranty.


Specifications

Model	ASHEAX-40
Type	Microcontroller based analog process indicator on Digital display.
Input Signals / Sensor	4 to 20 mA DC, AC/DC Voltage, AC/DC Current, Resistance, Strain-gauge, Frequency, Proximity Switches and all temperature sensors like RTD Pt-100, Thermocouples type J,K,R,S,T,E,B, etc.
Display	4-digit, 0.5" seven-segment LED display.
Scale Range	-999 to +9999.
Calibration	Configurable.
Response time	< 100 mS
Linearity	0.1% of span.
Calibration facility	By Membrane keypad on front panel.
Accuracy	0.1% of FSD.
Retransmission	4 to 20 mA DC [optional].
Load driving capacity	600 Ohms
Polarity	Auto-sensing.
Settings	Settings for Zero, Span, Decimal point.
Dimensions	72x72x68 mm [W x H x D].
Execution	Panel mounting.
Enclosure	Industrial grade ABS.
Weight	Approximately 0.5 Kgs.
Operating Temperature	0 to 50 °C.

Features

- Microcontroller based design.
- Standard analog signals and Sensors.
- Digital LED displays.
- Low Input impedance – negligible load on loop.
- High accuracy and linearity to input signal
- 4-digit seven-segment displays
- Very low power consumption and heat dissipation
- Fully configurable
- Retransmission option.
- External transmitter powering option
- Auto-sensing polarity
- Selectable Decimal point
- Multiple Relay output options
- Rugged, industrial grade ABS enclosure
- Compact and rugged execution
- High Noise immunity.
- Panel / Field / Hazardous-area installation in IP65 execution
- Available in several DIN standard dimensions
- Proven record of several thousand installations
- Lifetime warranty on design and workmanship

DIMENSIONAL DIAGRAM



HOW TO ORDER

72x72x68 mm, No Relays.

AX-40

Configuration and Add-on options w

1 INPUT SIGNALS

- ▶ 4 to 20 mA DC
- ▶ 0 to 20 mA DC
- ▶ 4 to 20 mA DC with aux 24 VDC @ 100 mA power output for Trans.
- ▶ RTD Pt-100 (three-wire)
- ▶ J type Thermocouple (0 to 750 OC)
- ▶ K type Thermocouple (0 to 1200 OC)
- ▶ R type Thermocouple (0 to 1800 OC)
- ▶ S type Thermocouple (0 to 1800 OC)
- ▶ T type Thermocouple (-200 to +350 OC)
- ▶ DC Voltage (To be specified)
- ▶ Resistance
- ▶ Frequency, Proximity Sensor.
- ▶ AC Voltage (to be specified)
- ▶ AC Current (0 to 1 / 5 Ampere)
- ▶ Other (to be specified).

L
M
Q
R
J
K
P
S
T
D
E
F
H
A
Z

2 POWER SUPPLY

- ▶ 230 V AC (±10%), 50 Hz (±10%).
- ▶ 110 V AC (±10%), 60 Hz (±10%).
- ▶ 24 V DC (±10%).
- ▶ Other (to be specified).

S
H
D
Z

3 EXECUTION

- ▶ DIN Rail mounting
- ▶ Panel mounting [48 x 48 mm]
- ▶ Panel mounting [48 x 96 mm]
- ▶ Panel mounting [72 x 72mm]
- ▶ Panel mounting [96 x 96 mm]
- ▶ Field mounting in Weather-proof execution (Polycarbonate enclosure, IP65 protection)
- ▶ Field mounting in Flame/Explosion-proof execution (Cast Aluminum Alloy LM6 enclosure, for Gas groups IIA, IIB)
- ▶ Other (to be specified)

N
A
B
C
D
W
X
Z

4 RETRANSMISSION

- ▶ Retransmission of 4 to 20 mA DC
- ▶ Retransmission of 0 to 10 V DC
- ▶ No Retransmission
- ▶ Other (to be specified)

R
V
O
Z

OUR OTHER PRODUCTS



PROCESS CONTROLLER

UNIVERSAL CONTROLLER

FLOW TOTALIZER

TEMP. SCANNER

SIGNAL ISOLATORS & TRANSDUCERS

SMPS POWER SUPPLIES

ASHE CONTROLS PRIVATE LIMITED

6/317, 318 & 319, Jogani Industrial Complex, Near ATI, Sion-Trombay Road, Sion, Mumbai - 400 022, India.
Phone / Fax : (022) 2405 1561, 2405 5791 • E-mail : sales@ashecontrols.com • Website: http://www.ashecontrols.com