

# LOOP POWERED INDICATORS

## MEX-408



### Overview

The ASHE Model MEX-408 Digital process Indicator is a compact, rugged and reliable indicating instrument which is specifically designed for accurate process measurement applications in areas without power availability.

The Indicator accepts an industrial standard current input signal of 4 to 20 mA DC and displays the actual process value calibrated in the desired units, on a linear scale. The process value is displayed on a 4-Digit seven-segment LED digital display module. There is no necessity of any external Power Supply.

The instrument can be calibrated on any scale range from 9999 to +9999 units.

The Ashe MEX-408 Indicator is therefore an ideal single unit substitute to conventional analog indicators because of its inherent accuracy in process control, besides other superior characteristics like total immunity to Shocks, Dust, Ambient temperatures, Humidity and Corrosive atmospheres. Its unique feature is that it is completely current loop-driven, eliminating the requirement of any external power supply source and associated cabling.

Further, the instrument is manufactured using selected high-grade components which guarantee its reliability and long operational life. The unit also has no moving parts, which greatly enhances its versatility.

### Specifications

<b>Model</b>	ASHE MEX-408.
<b>Type</b>	Digital Loop Powered Indicator.
<b>Principle</b>	Signal amplification and self powering.
<b>Input Signal</b>	4 to 20 mA DC.
<b>Linearity</b>	0.1%.
<b>Calibration facility</b>	Zero and Span settings [external].
<b>Accuracy</b>	0.1%.
<b>Indication</b>	4-digit LED display.
<b>Display height</b>	0.4".
<b>Forward voltage drop</b>	5.5 Volts @ 20 mA.
<b>Sensing resistance</b>	6.00 Ohms.
<b>Polarity</b>	Auto-sensing.
<b>Settings</b>	Zero, Span, Decimal point.
<b>Response Time</b>	Typically 75 mSec.
<b>Power Supply</b>	Nil (Loop powered).
<b>Calibration Range</b>	To be specified.
<b>Dimensions</b>	48 x 96 x 75 mm. [H x W x D].
<b>Execution</b>	Panel mounting.
<b>Enclosure</b>	Industrial grade ABS.
<b>Weight</b>	Approximately 0.2 Kgs.
<b>Operating Temperature</b>	0 to 50 °C.

### Features

- No external power supply required.
- Standard 4 to 20 mA DC current loop powered operation
- Low Input impedance – negligible load on loop.
- High accuracy and linearity to input signal
- 3-½, 4 and 4-½ digit displays
- Very low power consumption and heat dissipation
- Low forward voltage drop
- Auto-sensing polarity
- Selectable Decimal point
- LCD / LED display
- Front accessible Zero and Span calibration
- Rugged, industrial grade ABS enclosure
- Compact and rugged execution
- Panel / Field / Hazardous-area installation in IP65 execution
- Available in several dimensions
- Current limiting for I/O protection
- Proven record of several thousand installations
- Lifetime warranty on design and workmanship

### ASHE CONTROLS PRIVATE LIMITED