


STREAM SELECTOR

FOR ANALYTICAL APPLICATIONS

STL-94 | STL-96

PRECISION CONTROL



Overview

The ASHE STL series is a micro-controller based Stream Selector with control Relay outputs and Analog signal outputs, offered in a highly compact, rugged and reliable execution. The instrument has six keys on the front panel, with which the operator can set the parameters and configure the instrument as desired.

The instrument controls stream selection of up to six streams in analytical applications, using control Relay outputs for each stream, which can be synchronized by external Pulse or Timer. The instrument also provides analog outputs on Sample and Hold basis for each Stream. LED indications are provided on the front panel for status of Streams, Low and High Alarms of each channel.

The instrument offers a comprehensive display of parameters and menu selections on a brightly backlit 20-character x four-line LCD display. Options include Auto and Manual modes, Pulse or Timer based sequencing, etc. The instrument operates on universal AC power supply (90 to 270 V AC, 50/60 Hz) and is offered in standard 1/2 DIN panel-mount execution. The instrument has non-volatile memory.

Other features include its inherent accuracy and immunity to shocks, dust, ambient temperatures, and humidity. It is available in field-mounting (weather-proof) execution and standard panel mounting enclosures. Further, the instrument is manufactured using selected high-grade components which guarantee its functionality and long operational life.

All ASHE range of instruments carry a lifetime warranty for design and workmanship.

Specifications

Model	STL-94 [Four-Stream] STL-96 [Six-Stream]
Type	Micro-controller based sequential Stream Selector.
Input Signal	Analog 4 to 20 mA DC Digital Pulse Input (For Stream Selection) Number of Streams: Four / Six.
Display	20 x 4 Alphanumeric LCD Display with white Backlight and Black Text. 4 nos. LEDs for status of Streams 4 nos. LEDs for indication of Low Alarm 4 nos. LEDs for Indication of High Alarm 3 nos. LEDs for Status Indication (Auto, Manual & Pause) 1 no. Bi-colour LED for Start/Stop status indication
Scale Range	0000 to 9999 (Selectable)
Response time	Typically 500 mS.
Relay Outputs	For Streams 4/6 Potential-Free Relay Contacts For Low Alarm 4/6 Potential-Free Relay Contacts For High Alarm 4/6 Potential Free Relay Contacts
Contact rating	10 Ampere @ 230 V AC (Resistive Loads).
Memory	Non-Volatile (on EEPROM).
Settings	By six nos. of touch sensitive keys on front panel.
Settable Features	Control Logic, Set points, Hysteresis etc.
Accuracy	1% FSD.
Power Supply	90 to 270 V AC, 50 Hz, universal AC power.
Enclosure	Panel mounting.
Bezel Dimensions	192 x 96 mm [1/2 DIN]
Cut-out Dimensions	188 x 92 mm
Depth	200 mm
Weight	Approximately 1.5 kgs.

Features

- Microcontroller based design.
- Four-Stream and Six-Stream options
- Bright 20-character x Four-line LCD display
- Auto and Manual operations
- High accuracy and linearity to input signal
- Control Relay output for each Stream
- Fully configurable
- Retransmission of each stream signal.
- Sample and Hold facility for non-active channels
- Channel Skip feature
- Universal AC Power Supply
- Rugged, industrial grade ABS enclosure
- High Noise immunity.
- Panel / Field installation in IP65 execution
- Proven record of installations
- Lifetime warranty on design and workmanship

ASHE CONTROLS PRIVATE LIMITED

6/317, 318 & 319, Jogani Industrial Complex, Near ATI, Sion-Trombay Road, Sion, Mumbai - 400 022, India.
Phone / Fax : (022) 2405 1561, 2405 5791 • E-mail : sales@ashecontrols.com • Website: <http://www.ashecontrols.com>