

PESO
CERTIFIED



MMX-408 Loop Powered LED Indicator

OVERVIEW

The Model MMX-408 Digital process Indicator is a compact, rugged and reliable indicating instrument which is specifically designed for accurate process measurement applications in hazardous areas.

The microcontroller based Intrinsically Safe Indicator accepts an industrial standard current input signal of 4 to 20 mA DC and displays the actual process value calibrated in the desired units, on a linear scale. The process value is displayed on a 4-Digit seven-segment LED digital display module. There is no necessity of any external Power Supply.

The instrument can be calibrated on any scale range from -999 to +9999 units.

The MMX-408 Indicator is therefore an ideal single unit substitute to conventional analog indicators because of its inherent accuracy in process measurement, besides other superior characteristics like total immunity to Shocks, Dust, Ambient temperatures, Humidity and Corrosive atmospheres. Its unique feature is that it is completely current loop-driven, eliminating the requirement of any external power supply source and associated cabling.

Further, the instrument is manufactured using selected high-grade components which guarantee its reliability and long operational life.

SPECIFICATIONS

Model	MMX-408.
Type	Microcontroller based Intrinsically Safe Digital Loop Powered Indicator.
Principle	Signal amplification and powering.
Input Signal	4 to 20 mA DC.
Linearity	± 0.1%.
Calibration facility	Zero and Span settings [external].
Accuracy	± 0.1%.
Indication	4-digit LED display.
Display height	0.4".
Forward voltage drop	5.5 Volts @ 20 mA.
Sensing resistance	6.00 Ohms.
Polarity	Auto-sensing.
Settings	Zero, Span, Decimal point.
Response Time	Typically 75 mSec.
Power Supply	Nil (Loop powered).
Calibration Range	To be specified.
Dimensions	110 x 110 x 100 mm. [H x W x D].
Execution	Hazardous area installation.
Enclosure	Certified Explosion-proof Aluminium Alloy LM6, suitable for gas groups IIA/IIB, Zone 1 & 2.
Ingress Protection	IP66
Mounting accessories (optional)	Stainless Steel Mounting Kit comprising 2" pipe mounting bracket, U-Clamp, Angle bracket and mounting bolt.
Weight	Approximately 0.5 Kgs.
Operating Temperature	0 to 50°C.

FEATURES

- No external power supply required.
- Standard 4 to 20 mA DC current loop powered operation
- Low Input impedance – negligible load on loop.
- High accuracy and linearity to input signal
- 4-digit LED display
- Intrinsically Safe design.
- Very low power consumption and heat dissipation
- Low forward voltage drop
- Auto-sensing polarity
- Selectable Decimal point
- Front accessible Zero and Span calibration on membrane keypad
- Rugged, industrial grade Aluminum LM6 enclosure
- Compact and rugged execution
- Hazardous-area installation for IIA/IIB in IP65 execution
- Available in several dimensions
- Current limiting for I/O protection
- Proven record of several thousand installations
- Lifetime warranty on design and workmanship